

Google Maps location from address

On this page

- [Features used to implement the example](#)
- [Example: Google Maps location for an address](#)
 - [Text to be parsed](#)
- [Other examples of this custom field](#)
- [Related Usage Examples](#)

Features used to implement the example

- [Calculated Text Field](#)

Example: Google Maps location for an address

Show the Google map location for an address. The address is stored in another custom field **Address** (Text Field (single line)).

A valid configuration for this **Calculated Text Field**:

Parsing Mode: ?

☐ Basic

Basic mode: Insert field codes anywhere in the text, and they will be replaced with corresponding field values. Field code formats are `{nnnnn}`, and `{nnnnn.i}` for Cascading Select fields (i = 0 for base level).

☒ Advanced

Advanced mode: Strings literals are written in double quotes ("This is a string."). Operator '+' is used to concatenate strings, and field codes are like in basic mode, e.g. "Issue key is " + `{00015}` + ". ". More information at [parser syntax documentation](#).

Text to be parsed for Calculated Text Field: [Line 1 / Col 1] [Syntax Specification](#) [Check Syntax](#)

```
1 {10407} != null ? "<iframe width=\"100%\" height=\"500\" id=\"gmap_canvas\" src=\"https://maps.google.com/maps?q=\" + replaceAll(toLowerCase({10407}), \"\", \"%20\") + \"&t=&z=13&ie=UTF8&iwloc=&output=embed\" frameborder=\"0\" scrolling=\"no\" marginheight=\"0\" marginwidth=\"0\"></iframe>\" : null
```

Start typing to get the list of available fields

Insert String Value

Start typing to get the list of available fields

Insert Numeric Value

Text to be parsed

- `{10407} != null ? "<iframe width=\"100%\" height=\"500\" id=\"gmap_canvas\" src=\"https://maps.google.com/maps?q=\" + replaceAll(toLowerCase({10407}), \"\", \"%20\") + \"&t=&z=13&ie=UTF8&iwloc=&output=embed\" frameborder=\"0\" scrolling=\"no\" marginheight=\"0\" marginwidth=\"0\"></iframe>\" : null`

Note that:

- `{10407}` is the field code for **Address**

Once configured and added to an issue screen, the result will look like this:


Jira Workflow Toolbox / JWT-1

Google Maps location for an address

Edit
Comment
Assign
More
To Do
In Progress
Done
Admin

Details

Type:

Story

Priority:

Highest

Affects Version/s:

None

Labels:

[MeetTheMonsters](#)
[ToolboxesForEveryNeed](#)
[xApps](#)

Epic Link:

Jira Workflow Toolbox

Address:

Atlassian Sydney

Google Map (by JWT):



Status:

TO DO (View Workflow)

Resolution:

Unresolved

Fix Version/s:

Version 2.0

Other examples of this custom field

Page: [Google Maps location from address](#)
 Page: [Highest value of a custom field among linked issues](#)
 Page: [Number of linked bugs \(with hyperlink\)](#)
 Page: [Show timeliness of an issue based on two date pickers](#)
 Page: [Show timeliness of an issue based on two date pickers](#)

Related Usage Examples

- Using project properties to calculate custom sequence numbers
 - example
 - post-function
 - calculated-field
 - project-properties
- Number of open subtasks
 - example
 - calculated-field
- Setting the priority depending on the multiplication of custom fields
 - example
 - calculated-field
 - post-function
- Total of all story points in an epic
 - example
 - custom-field
 - calculated-field
- Show timeliness of an issue based on two date pickers
 - example
 - custom-field
 - calculated-field
- Highest value of a custom field among linked issues
 - example
 - custom-field
 - calculated-field
- Predicted due date of an epic
 - example
 - calculated-field
- Number of issues in same version
 - example
 - calculated-field
- Number of linked bugs (with hyperlink)
 - example
 - calculated-field
- Google Maps location from address

- example
 - calculated-field
 - custom-field
- Total remaining estimate in an epic
 - example
 - calculated-field