Remove versions selected in a version picker custom field

On this page

- Features used to implement the example
- Example: Remove versions selected in a version picker custom field
- Other examples of that function
- Related Usage Examples


Features used to implement the example

- **Copy parsed text to a field**


Example: Remove versions selected in a version picker custom field

We have a custom field that holds a version value (with Version Picker). As part of certain workflow steps, I'd like the current value to be removed, and the field reset back to "None".

You can use **Copy parsed text to a field** and set the field **Text to be parsed and the copied to target field** with the following value "**- %{10800}**" (removing the double quotes), provided **10800** is the **ID** of the version picker custom field you want to clear. What you are doing here is removing (by the leading '-' character) the versions currently selected in **Version Picker custom field**.



Once configured the transition looks like this:



Other examples of that function

Page: Add all assignees of certain sub-task types to a "Multi-User Picker" custom field
Page: Add and remove a single or a set of items from multi valued fields

Related Usage Examples

- Validate compatible values selection among dependent custom fields
  - example

Page: Add current user to comment
Page: Add or remove request participants
Page: Add watchers from a part of the issue summary: "Summary_text - watcher1, watcher2, watcher3, ..."
Page: Assign issue based on the value of a Cascading Select custom field
Page: Assign issue to last user who executed a certain transition in the workflow
Page: Automatically close resolved sub-tasks when parent issue is closed
Page: Automatically reopen parent issue when one of its sub-tasks is reopened
Page: Calculate the time elapsed between 2 transition executions
Page: Close parent issue when all sub-tasks are closed
Page: Combine the values of several Multi-User picker fields
Page: Compose a parsed text including the "full name" or a user selected in a User Picker custom field
Page: Compose dynamic text by inserting field values in a text template
Page: Copy issue labels to a custom field
Page: Copy the value of a user property into a user picker
Page: Create a comment in sub-tasks when parent transitions
Page: Execute transition in epic
Page: Getting the number of selected values in a custom field of type Multi Select
Page: Limit the number of hours a user can log per day
Page: Make a sub-task's status match parent issue's current status on creation
Page: Make parent issue progress through its workflow
Page: Moving story to "In Progress" when one of its sub-tasks is moved to "In Progress"
Page: Moving story to "Ready for QA" once all its sub-tasks are in "Ready for QA" status
Page: Parse Email adresses to watchers list
Page: Parsing text from last comment and appending it to issue's summary
Page: Remove versions selected in a version picker custom field
Page: Replace certain issue link types with different ones
Page: Restrict parent issue from closing if it has sub-tasks that were created during a given parent issue status
Page: Set a Select or Multi-Select field using regular expression to express the values to be assigned
Page: Set assignee depending on issue type
Page: Set field depending on time passed since issue creation
Page: Set priority for issues that have been in a certain status for longer than 24 hours
Page: Set security level based on groups and project roles the reporter or creator are in
Page: Transition linked issues in currently active sprint
Page: Transition only a sub-task among several ones
Page: Transition parent issue only when certain issue sub-task types are done
Page: Update Cascading Select custom field with a value of the field in parent issue
Page: Update checkboxes custom field if a file has been attached during a transition
Page: Validation on issue attachments
Page: Validation on MIME types of issue attachments
Page: Writing a comment to blocked issues when blocking issues are resolved

- validator
- custom-field

- Validate a custom field "Story Points" has been given a value in Fibonacci sequence
  - example
  - validator
  - custom-field
- Validate that multi-user picker custom field A does not contain any user in multi-user picker custom field B
  - example
  - validator
  - custom-field
- Validation on the value of a Cascading Select field
  - example
  - validator
  - custom-field
- Make different fields mandatory depending on the value of a Select List custom field
  - example
  - validator
  - custom-field
- Make a custom field mandatory when priority is "Critical" or "Blocker" and issue type is "Incident"
  - example
  - validator
  - custom-field
- Enforce a field (Select List) to be set when another field (Radio Button) has a certain value (works with any kind of field type)
  - example
  - validator
  - custom-field
- Make attachment mandatory depending on the value of certain custom field
  - example
  - validator
  - custom-field
- Create a dynamic set of sub-tasks based on checkbox selection with unique summaries
  - example
  - post-function
  - custom-field
  - sub-task
- Total of all story points in an epic
  - example
  - custom-field
  - calculated-field
- Show timeliness of an issue based on two date pickers
  - example
  - custom-field
  - calculated-field
- Add and remove a single or a set of items from multi valued fields
  - example
  - post-function
  - custom-field
  - issue-links
  - sub-task
- Highest value of a custom field among linked issues
  - example
  - custom-field
  - calculated-field
- Google Maps location from address
  - example
  - calculated-field
  - custom-field
- Make certain custom field required in resolve screen only if the resolution was set to "Fixed"
  - example
  - validator
  - custom-field