

Moving story to "Ready for QA" once all its sub-tasks are in "Ready for QA" status (Transition issues)

On this page

- Features used to implement the example
- Example: Moving story to "Ready for QA" once all its sub-tasks are in "Ready for QA" status (Transition issues)
- Other examples of that function
- Related Usage Examples

Features used to implement the example

- Transition issues

Example: Moving story to "Ready for QA" once all its sub-tasks are in "Ready for QA" status (Transition issues)

When **all** sub-tasks of a story are moved to "**Ready for QA**", the story should move from "**In Progress**" to "**Ready for QA**". Insert [Transition issues](#) post-function into transition from "**In Progress**" to "**Ready for QA**" in sub-task's workflow:

| | |
|---|--|
| Target Issues: Select the issue(s) to be transitioned. | Issue Selection Mode: <div><input type="radio"/> Current Issue <input checked="" type="radio"/> Parent Issue <input type="radio"/> Linked Epic <input type="radio"/> Linked Issues <input type="radio"/> Subtasks <input type="radio"/> Sibling Subtasks <input type="radio"/></div> <div>Issues under Epic <input type="radio"/> Sibling issues under Epic <input type="radio"/> JQL Query <input type="radio"/> Issue List</div> <div>Parent of current issue. If current issue is not a subtask, nothing will happen.</div> |
| Choose Action: Choose the action to be performed. | Action type: <div><input type="radio"/> Execute Transition <input checked="" type="radio"/> Transition to Status</div> <div>Select the status you want to transition target issue to. Available transitions from current status to selected destination status are retrieved, and sequentially tried out until one of them is executed successfully. If no transition to selected destination status is available, nothing will happen.</div> <div>Destination Status: Ready for QA</div> |
| Transition options: | <div><input type="checkbox"/> Skip conditions: conditions in transition to be executed will be ignored.</div> <div><input type="checkbox"/> Skip validations: validations in transition to be executed will be ignored.</div> <div><input type="checkbox"/> Skip transition permissions: user executing this post-function won't need 'Transition Issues' permission.</div> <div><input type="checkbox"/> Delayed execution: transition will be executed with a custom delay after current transition has finished.</div> |
| Conditional execution: Optional boolean expression that should be satisfied in order to actually execute the post-function. (Syntax Specification) | <div>1 <code>count(siblingSubtasks()) = count(filterByStatus(siblingSubtasks(), "Ready for QA"))</code></div> <div>Leave the field empty for executing the post-function unconditionally. Collection of Examples [Line 1 / Col 84]</div> <div>Logical connectives: and, or and not. Alternatively you can also use &, and !.</div> <div>Comparison operators: =, !=, >, >=, < and <=. Operators in, not in, any in, none in, ~ and !~ can be used with strings, multi-valued fields and lists.</div> <div>Logical literals: true and false. Literal null is used with = and != to check whether a field is initialized, e.g. {00012} != null checks whether Due Date is initialized.</div> <div>String Field Code Injector: Start typing to get the list of available fields</div> <div>Numeric/Date Field Code Injector: Start typing to get the list of available fields</div> <div>Check Syntax</div> |

Text to be parsed is: `count(siblingSubtasks()) = count(filterByStatus(siblingSubtasks(), "Ready for QA"))`

That boolean expression checks that all the sub-tasks are already at "**Ready for QA**" status. It is also possible to check the sub-tasks against more status, e.g. "**QA Accepted**" and "**Done**". In this case the following expression can be used:

```
count(siblingSubtasks()) = count(filterByStatus(siblingSubtasks(), "Ready for QA, QA Accepted, Done"))
```

Other examples of that function

Page: [Automatically close resolved sub-tasks when parent issue is closed](#)
Page: [Automatically close resolved sub-tasks when parent issue is closed \(Transition issues\)](#)
Page: [Change parent's status depending on sub-task's summary](#)
Page: [Change parent's status depending on sub-task's summary \(Transition issues\)](#)
Page: [Moving story to "In Progress" when one of its sub-tasks is moved to "In Progress"](#)
Page: [Moving story to "In Progress" when one of its sub-tasks is moved to "In Progress" \(Transition issues\)](#)
Page: [Moving story to "Ready for QA" once all its sub-tasks are in "Ready for QA" status](#)
Page: [Moving story to "Ready for QA" once all its sub-tasks are in "Ready for QA" status \(Transition issues\)](#)
Page: [Moving sub-tasks to "Open" status when parent issue moves to "In Progress"](#)
Page: [Moving sub-tasks to "Open" status when parent issue moves to "In Progress" \(Transition issues\)](#)
Page: [Transition only a sub-task among several ones](#)
Page: [Transition only a sub-task among several ones \(Transition issues\)](#)
Page: [Transition sub-tasks when parent is transitioned](#)
Page: [Transition sub-tasks when parent is transitioned \(Transition issues\)](#)
Page: [Triage Jira Service Desk email requests \(Move issues\)](#)

Related Usage Examples

- [Moving story to "In Progress" when one of its sub-tasks is moved to "In Progress" \(Transition issues\)](#)
 - [example](#)
 - [post-function](#)
 - [transition](#)
- [Transition sub-tasks when parent is transitioned](#)
 - [example](#)
 - [post-function](#)
 - [sub-task](#)
 - [transition](#)
 - [outdated](#)
- [Transition only a sub-task among several ones](#)
 - [example](#)
 - [post-function](#)
 - [sub-task](#)
 - [transition](#)
 - [outdated](#)
- [Moving sub-tasks to "Open" status when parent issue moves to "In Progress"](#)
 - [example](#)
 - [post-function](#)
 - [sub-task](#)
 - [transition](#)
 - [outdated](#)
- [Moving story to "Ready for QA" once all its sub-tasks are in "Ready for QA" status](#)
 - [example](#)
 - [post-function](#)
 - [sub-task](#)
 - [transition](#)
 - [outdated](#)
- [Change parent's status depending on sub-task's summary \(Transition issues\)](#)
 - [example](#)
 - [post-function](#)
 - [transition](#)
- [Automatically close resolved sub-tasks when parent issue is closed](#)
 - [example](#)
 - [post-function](#)
 - [sub-task](#)
 - [transition](#)
 - [outdated](#)
- [Change parent's status depending on sub-task's summary](#)
 - [example](#)
 - [post-function](#)
 - [sub-task](#)
 - [transition](#)
 - [outdated](#)
- [Moving story to "In Progress" when one of its sub-tasks is moved to "In Progress"](#)
 - [example](#)
 - [post-function](#)
 - [sub-task](#)
 - [transition](#)
 - [outdated](#)
- [Automatically close resolved sub-tasks when parent issue is closed \(Transition issues\)](#)
 - [example](#)
 - [post-function](#)
 - [transition](#)
- [Close parent issue when all sub-tasks are closed](#)
 - [example](#)
 - [condition](#)
 - [validator](#)
 - [post-function](#)

- sub-task
 - transition
- Moving sub-tasks to "Open" status when parent issue moves to "In Progress" (Transition issues)
 - example
 - post-function
 - transition
- Transition sub-tasks when parent is transitioned (Transition issues)
 - example
 - post-function
 - transition
- Transition only a sub-task among several ones (Transition issues)
 - example
 - post-function
 - transition
- Moving story to "Ready for QA" once all its sub-tasks are in "Ready for QA" status (Transition issues)
 - example
 - post-function
 - transition