

Create a static set of sub-tasks with unique summaries

On this page

- [Features used to implement the example](#)
- [Example: Create a static set of sub-tasks with unique summaries](#)
- [Other examples of that function](#)
- [Related Usage Examples](#)

Features used to implement the example

- [Create issues and sub-tasks](#)
-

Example: Create a static set of sub-tasks with unique summaries

In this example, multiple sub-tasks with unique summaries are added to an issue on issue creation, e.g.

Creating issue "Release x.y.z" should automatically create sub-tasks

- "Documentation for Version x.y.z"
- "Blog entry for Version x.y.z"
- "Newsletter for Version x.y.z"
- "Social Media for Version x.y.z"

The configuration will look like this:

Issues to be created: Sets the number of issues that will be created.	Only one issue Multiple issues based on seeds: Math Expression Math expression (Syntax Specification and Examples) 14 Input a mathematic expression returning the number of issues you want to be created. From here on, you will be able to obtain the order of creation (seed number, starting by 1) of each issue being created using ^. String Field Code Injector: Start typing to get the list of availabe fields Numeric/Date Field Code Injector: Start typing to get the list of availabe fields	Check Syntax [Line 1 / Col 3]
Issue Type: Sets the issue type of the issues to be created.	Selected Issue Type Issue Type Name (standard issue) Issue Type Name (subtask) Sub-task	
Parent Issue: Sets the parent of the sub-tasks to be created.	Current Issue	
Summary: Sets the summary of the issues to be created.	Parsing mode: basic advanced getMatchingValue(^,[1,2,3,4], ["Documentation for Version " + %{00074}, "Blog entry for Version " + %{00074}, "Newsletter for Version " + %{00074}, "Social Media for Version " + %{00074}]) Strings literals are written in double quotes ("This is a string, "). Operator '+' is used to concatenate strings, and field codes are like in basic mode, e.g., "Issue key is " + %{00015} + ". ". More information at parser syntax documentation. String Field Code Injector: Start typing to get the list of availabe fields Numeric/Date Field Code Injector: Start typing to get the list of availabe fields Field code injectors reference: Current issue Seed issue Parent of new sub-task	Check Syntax [Line 1 / Col 1]
Description: Sets the description of the issues to be created.	Parsing mode: basic advanced 1 Insert field codes anywhere in the text, and they will be replaced with corresponding field values. Field code formats are %{nnnn}, and %{nnnn.1} for Cascading Select fields (i = 0 for base level). String Field Code Injector: Start typing to get the list of availabe fields Numeric/Date Field Code Injector: Start typing to get the list of availabe fields Field code injectors reference: Current issue Seed issue Parent of new sub-task	Check Syntax [Line 1 / Col 1]

Set Fields:
Sets field values in the new issues.

Field to be set:

Start typing to get the list of available fields

Add

Field	Type of Value	Value	Actions
-------	---------------	-------	---------

Inherit Remaining Fields:
Inherit field values from other issues, for those fields that has not been set in the previous section.

Don't inherit field values

Issue Links:
The newly created issues can be linked to other issues.

Add Issue Link

Issue Link Type	Linked Issues	Condition	Actions
-----------------	---------------	-----------	---------

Additional Actions:
Optional actions that will be executed after all issues have been created.

☐ Save issue keys of created issues into *Ephemeral String 3* virtual field as a comma separated list.

Conditional execution:
Optional boolean expression that should be satisfied in order to actually execute the post-function.
[\(Syntax Specification\)](#)

1

%{00014} = "Release"

Leave the field empty for executing the post-function unconditionally.

Collection of Examples

[Line 1 / Col 1]

Logical connectives:

Comparison operators:

Logical literals:

Check Syntax

String Field Code Injector:

Numeric/Date Field Code Injector:

Start typing to get the list of available fields

Start typing to get the list of available fields

As four subtasks are always to be created in total, the **Issues to be created** option is set to **Math Expression** with the value **4**.

The dynamic summaries are parsed with the following expression:

```
getMatchingValue(^, [1,2,3,4],
["Documentation for Version " + %{00074},
"Blog entry for Version " + %{00074},
"Newsletter for Version " + %{00074},
"Social Media for Version " + %{00074}])
```

Note that:

- **%{00074}** is the field code for **"Fix Version/s"**

Since this behaviour should only occur with release issues, the following Conditional execution is added: **%{00014} = "Release"**

Note that:

- **%{00074}** is the field code for **"Issue Type"**

Once configured, the transition will look like this:

Create

→

TODO

This is the **initial** transition in the workflow.

Screen: None - initial transition does not have a view.

Validators 1

Post Functions 4

The following will be processed after the transition occurs

Add post function

- Creates the issue originally.
- Re-index an issue to keep indexes in sync with the database.
- Fire a **Issue Created** event that can be processed by the listeners.
- Create as many issues as the **numeric value** returned by the following **mathematical** expression:

4

Issue type: **Sub-task**
Parent issue: **Current Issue**
Summary: text in **advanced** parsing mode
`getMatchingValue(^, [1,2,3,4], ["Documentation for Version " + ${Fixed versions}, "Blog entry for Version " + ${Fixed versions}, "Newsletter for Version " + ${Fixed versions}, "Social Media for Version " + ${Fixed versions}])`
Description: text in **basic** parsing mode

Post-function will only be executed if the following boolean expression is satisfied: `${Issue type} = "Release"`
 This feature will be run as user in field **Current user**. by JWT

After issue creation, the issue will look like this:


Software / SOFT-36

Release 1.2.3

 Edit
  Comment
 Assign
More ▾
Admin ▾


 Export ▾

Details

Type:  Release

Status: TODO [\(View Workflow\)](#)

Priority:  Low

Resolution: Unresolved

Affects Version/s: None

Fix Version/s: 1.2.3

Labels: None 

Description

[Click to add description](#)

Attachments

 Drop files to attach, or [browse](#).

Sub-Tasks

1. Documentation for Version 1.2.3	 TODO Unassigned
2. Blog entry for Version 1.2.3	 TODO Unassigned
3. Newsletter for Version 1.2.3	 TODO Unassigned
4. Social Media for Version 1.2.3	 TODO Unassigned

People

Assignee:  Unassigned
[Assign to me](#)

Reporter:  admin

Votes: 0

Watchers: 1 [Stop watching this issue](#)

Dates

Created: 5 minutes ago

Updated: 5 minutes ago

Other examples of that function

[Page: Assign new issues to a different project role depending on field value in current issue](#)
[Page: Clone an issue and all its subtasks \(with additional restrictions\)](#)
[Page: Create 3 issues in 3 different projects](#)
[Page: Create a dynamic set of sub-tasks based on checkbox selection with unique summaries](#)
[Page: Create a static set of sub-tasks with unique summaries](#)
[Page: Create a story for each component in an epic](#)
[Page: Create a sub-task for each user selected in a Multi-User Picker](#)
[Page: Create a sub-task in each story of an epic](#)
[Page: Create specific sub-tasks for each selected component](#)

Related Usage Examples

- [Creating a Jira Service Desk internal comment](#)
 - [example](#)
 - [post-function](#)
- [Limit the number of hours a user can log per day](#)
 - [example](#)
 - [validator](#)
 - [post-function](#)
 - [work-log](#)
- [Using project properties to calculate custom sequence numbers](#)
 - [example](#)
 - [post-function](#)
 - [calculated-field](#)
 - [project-properties](#)
- [Set a date based on current date](#)
 - [example](#)
 - [post-function](#)
- [Setting the priority depending on the multiplication of custom fields](#)
 - [example](#)
 - [calculated-field](#)
 - [post-function](#)
- [Parse Email addresses to watchers list](#)
 - [example](#)
 - [post-function](#)
- [Set the assignee based on a condition](#)
 - [example](#)
 - [post-function](#)
- [Create a dynamic set of sub-tasks based on checkbox selection with unique summaries](#)
 - [example](#)
 - [post-function](#)

- custom-field
 - sub-task
- Create a static set of sub-tasks with unique summaries
 - example
 - post-function
- Triage Jira Service Desk email requests (Move issues)
 - example
 - post-function
 - move
 - transition-issue
- Moving story to "In Progress" when one of its sub-tasks is moved to "In Progress" (Transition issues)
 - example
 - post-function
 - transition
- Transition sub-tasks when parent is transitioned
 - example
 - post-function
 - sub-task
 - transition
 - outdated
- Transition only a sub-task among several ones
 - example
 - post-function
 - sub-task
 - transition
 - outdated
- Moving sub-tasks to "Open" status when parent issue moves to "In Progress"
 - example
 - post-function
 - sub-task
 - transition
 - outdated
- Moving story to "Ready for QA" once all its sub-tasks are in "Ready for QA" status
 - example
 - post-function
 - sub-task
 - transition
 - outdated