Users, groups and roles

JWT comes with many dedicated functions to retrieve user-related data, from group or role memberships to issue assignments.

Available functions

Function	Output	Short description	Label
userDisplayName()	TEXT TEXT LIST	Returns the **full name** of a given user.	
defaultUserForRole()	TEXT	Returns the **user name** of the **default project role** user.	
lastAssigneeInRole()	TEXT	Returns the **user name** of the **last assignee** in a given **project role**.	
userEmail()	TEXT TEXT LIST	Returns the **email address(es)** of given users.	
usersWithEmail()	TEXT LIST	Returns the **user names** of users matching a given **email address**.	
usersInRole()	TEXT LIST	Returns **members** of a given **project role**.	STAFF PICK
usersInGroup()	TEXT LIST	Returns the **user names** of active users in a given group.	
userProperty()	TEXT	Returns the values of **user properties**.	
userFullName()	TEXT TEXT LIST	Returns the **full name** of a given user.	
rolesUserPlays()	TEXT LIST	Returns all **project roles** for given users.	
projectLeader()	TEXT	Returns the **project lead**	
projectLead()	TEXT	Returns the **project lead**	
nextUserInGroup()	TEXT	Returns the **name** of the **next active user** in a **group**.	
leastBusyUserInRole()	TEXT	Returns the **name** of the **user** in a given **project role** with the lowest number of **unresolved issues assigned**.	
isInGroup()	BOOLEAN	Checks whether **users** are a member of a specific **group**.	STAFF PICK
isActive()	BOOLEAN	Checks whether **users** are active	
groupsUserBelongsTo()	TEXT LIST	Returns all **groups** for given users.	
getUserKey()	TEXT	Returns the **user key** of a given user.	
fullNameToUser()	TEXT	Returns the **user name** for a given user.	
displayNameToUser()	TEXT	Returns the **user name** for a given user.	

isInRole()	BOOLEAN	Checks whether **users** are a member of a specific **project role**.

If you still have questions, feel free to refer to our support team.