

availableItems()

This function returns a **text list** with **available and enabled** 1st-level options of [selectable fields](#).
Disabled options will be ignored.

Syntax

```
availableItems(field) #Output: Text list
```

Examples

Parser expression	Description
<pre>availableItems(%{issue. securityLevel})</pre>	This example returns a text list with all security levels available for the project and current user.

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
field	<div>TEXT</div>	The parameter must be a valid field code for a selectable field .

Output

This function returns a comma-separated

TEXT LIST

 of **all enabled options** of the specified selectable field.

Variant of the function where you can optionally specify a **dedicated parent option**.
Only child options matching the specified parent will be returned.

Syntax

```
availableItems(field, parentOption) #Output: Text list
```

Examples

Parser expression	Description
-------------------	-------------

```
availableItems(%{issue.cf10100}, "Europe")
```

This example returns all **child options** of the **Europe** option in a custom cascading select field with the [field code](#) `issue.cf10100`.

Let's assume the custom field holds regions and is structured in the following way:

- Europe
 - **North**
 - South (disabled)
 - **East**
 - **West**
- US
 - Alabama
 - Alaska
 - ...

In this example the function would return "**North, East, West**".

Disabled options will be **ignored**.

Additional information

This function will return a comma-separated list of all **child options** of a **cascading select** field. Only child options (2nd level option) of the specified parent option will be returned.

Parameters used in this function

Parameter	Input (data type)	Description
field	<input type="text" value="TEXT"/>	The parameter must be a valid field code for a selectable field .
parentOption	<input type="text" value="TEXT"/>	The parameter must be a valid option name.

Output

This function returns a with **all available child options** of a specified cascading select field.

Only enabled options will be returned. If you want to **include disabled options**, please use the related function: [allAvailableItems\(\)](#)



Use cases and examples

Use case

No content found.