

allAvailableItems()

This function returns a **text list** with **all available** (parent) options of [selectable fields](#).

Syntax

```
allAvailableItems(field) #Output: Text list
```

Examples

| Parser expression | Description |
|---|---|
| <pre>allAvailableItems(\${issue.securityLevel})</pre> | This example returns a text list with all security levels available for the project and current user. |

Additional information

Parameters used in this function

| Parameter | Input (data type) | Description |
|-----------|-------------------|---|
| field | TEXT | The parameter must be a valid field code for a selectable field . |

Output

This function returns a comma-separated of **all options** of the specified selectable field.

Variant of the function where you can optionally specify a **dedicated parent option**. Only child options matching the specified parent will be returned.

Only to be used with cascading select fields.

Syntax

```
allAvailableItems(field, parentOption) #Output: Text list
```

Examples

| Parser expression | Description |
|-------------------|-------------|
| | |

```
allAvailableItems(${issue.cf10100}, "Europe")
```

This example returns all **child options** of the **Europe** option in a custom cascading select field with the [field code](#) issue.cf10100.

Let's assume the custom field holds regions and is structured in the following way:

- Europe
 - North
 - South (disabled)
 - East
 - West
- US
 - Alabama
 - Alaska
 - ...

In this example the function would return "**North, South, East, West**". Disabled options will also be returned.

Additional information

This function will return a comma-separated list of all **child options** of a **cascading select field**. Only child options (2nd level option) of the specified parent option will be returned.

Parameters used in this function

| Parameter | Input (data type) | Description |
|--------------|-------------------|---|
| field | TEXT | The parameter must be a valid field code for a selectable field . |
| parentOption | TEXT | The parameter must be a valid option name. |

Output

This function returns a [TEXT LIST](#) with **all child options** of a specified cascading select field.

All options will be returned. If you want to **exclude disabled options**, please use the related function: [availableItems\(\)](#)



Use cases and examples

Use case

No content found.