

# availableItems()

This function returns a **text list** with **available** and **enabled** 1st-level options of [selectable fields](#).

**Disabled** options will be ignored.

## Syntax

```
availableItems(field) #Output: Text list
```

## Examples

Parser expression	Description
<pre>availableItems(%{issue. securityLevel})</pre>	This example returns a <b>text list</b> with all <b>security levels</b> available for the project and current user.

## Additional information

Parameters used in this function

Parameter	Input (data type)	Description
field	TEXT	The parameter must be a valid <a href="#">field code</a> for a <a href="#">selectable field</a> .

## Output

This function returns a comma-separated  of **all enabled options** of the specified selectable field.

Variant of the function where you can optionally specify a **dedicated parent option**.

Only child options matching the specified parent will be returned.

## Syntax

```
availableItems(field, parentOption) #Output: Text list
```

## Examples

Parser expression	Description

```
availableItems({issue.  
cf10100}, "Europe")
```

This example returns all **child options** of the **Europe** option in a custom cascading select field with the [field code](#) issue.cf10100.

Let's assume the custom field holds regions and is structured in the following way:

- Europe
  - **North**
  - South (disabled)
  - **East**
  - **West**
- US
  - Alabama
  - Alaska
  - ...

In this example the function would return "**North, East, West**".

**Disabled options will be ignored.**

## Additional information

This function will return a comma-separated list of all **child options** of a **cascading select** field. Only child options (2nd level option) of the specified parent option will be returned.

Parameters used in this function

Parameter	Input (data type)	Description
field	TEXT	The parameter must be a valid <a href="#">field code</a> for a <a href="#">selectable</a> field.
parentOption	TEXT	The parameter must be a valid option name.

## Output

This function returns a [TEXT LIST](#) with **all available child options** of a specified cascading select field.

Only **enabled options** will be returned. If you want to **include disabled options**, please use the related function: [allAvailableItems\(\)](#)



## Use cases and examples

### Use case

No content found.