

previousValue()

This function returns the previous value of the given field for the current issue.

Syntax

```
previousValue(textField) #Output: Text
```

Examples

Parser expression	Description
<code>previousValue(%{issue.summary})</code>	This example returns the previous summary .
<code>previousValue(%{issue.priority})</code>	This example returns the previous priority .

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
textField	TEXT	Any given text field code.

Output

This function returns a TEXT

It will return **null** if the field was previously uninitialized.

Variant of **number** and **date-time** fields.

Syntax

```
previousValue(numberField) #Output: Number
```

Examples

Parser expression	Description
-------------------	-------------

<pre>previousValue({issue.dueDate})</pre>	<p>This example returns the previous due date.</p>
---	---

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
numberField	<input type="button" value="TEXT"/>	Any given numeric or date-time field code.

Output

This function returns a .

It will return **null** if the field was previously uninitialized.

Use cases and examples

Use case	JWT feature	Workflow function	Field type	Automated action	Parser functions
Add links to the issues in a ScriptRunner Issue Picker field				Create issue link action Delete issue link action	issueKeysToIssueList() toString() ngList() replaceAll() previousValue()
Set assignee based on a former assignee		Update or copy field values			previousValue()
Create an issue with a custom summary		Create issue			previousValue()
Prioritize the issues globally		Update or copy field values			indexOf() previousValue() issuesFromQL()