

# fieldHistory()

This function returns a **number list** with all the values that a **numeric** or **date-time field** has ever had in the past for current issue.

Values appear in the list in ascending ordered by setting time, i.e., older value has index 1, and most recent value has index `count(numberList)`. Uninitialized field statuses are not represented.

## Syntax

```
fieldHistory(numberField) #Output: Number list
```

## Examples

Parser expression	Description
<code>fieldHistory({issue.dueDate})</code>	This example returns: A <b>list</b> of all <b>due dates</b> that every have been set in the current issue.

## Additional information

Parameters used in this function

Parameter	Input (data type)	Description
numberField	TEXT	Any given numeric field code.

## Output

This function returns a

NUMBER LIST

Variant for **text fields**.

## Syntax

```
fieldHistory(textField) #Output: Text list
```

## Examples

Parser expression	Description
-------------------	-------------

```
fieldHistory(${issue.summary})
```

This example returns:

A **list** of all **summaries** that every have been set in the current issue.

## Additional information

Parameters used in this function

Parameter	Input (data type)	Description
textField	TEXT	Any given text field code.

## Output

This function returns a

TEXT LIST



## Use cases and examples

Use case	JWT feature	Workflow function	Field type	Automated action	Parser functions
Display historic due dates			Text		<code>toString()</code> <code>textOnNumberList()</code> <code>fieldHistory()</code> <code>dateToString()</code>