

Copy JWT project property

This post function **copies** the value of a **JWT project property** to a field. Read more about [JWT project properties](#).



Configuration

Project

Select the project that the property will be copied from. The following options are available:

Option	Description
Current project	The property value will be taken from the current project.
Selected project	Select a specific project the value will be taken from .
Set project manually (parser expression)	Specify the project using an expression. The Basic text mode is available where you can enter a text, and also use field codes. The expression must return a project key.

Property key

[JWT project properties](#) consist of a **key** and a **value**.

Specify the property **key** in this parameter. The corresponding **value** will be copied. The [Basic text mode](#) is available where you can enter a text, and also use field codes.

Target field

Select the **field** the project property value will be copied to.

If you want to **reuse the project property's value** in a following post function, you can select one of the [temporary text fields](#) as a target field and reference them later on.

Additional options

Choose to **update issues immediately** if you want Jira to fire a separate "Issue updated" event for any field change. This will also result in a dedicated **issue history** entry.

Conditional execution

You can **optionally** specify a [logical expression](#) to define the circumstances (or conditions) under which the post function should be executed.

The result of the logical expression must return a boolean value of either:

- **true** the post function will be executed
- **false** the post function will **not** be executed

Using the **conditional operator**, even complex or multi-layered conditions can be constructed.

Make sure to learn more about defining logical expressions and browse through the various **examples** here: [Logical mode](#)



Use cases and examples

Use case	JWT feature	Workflow function	Parser functions	Label
Set custom IDs for each issue		Set or create JWT project property Update or copy field values	length() projectProperty() substring() toNumber() year()	
Assign issue to the default user of a role		Assign to project role		
Calculate custom sequence numbers		Update or copy field values Set or create JWT project property	toUpperCase() substring() length() projectProperty() toNumber()	
Set specific default assignee if not set		Copy JWT project property		

If you still have questions, feel free to refer to our [support](#) team.