

usersWhoTransitioned()

This function returns the names of the users who transitioned the current issue from a **given status** to another **given status**, ordered by ascending transition time.

An empty text as an argument is interpreted as **any status**.

Syntax

usersWhoTransitioned(fromStatus, toStatus) #Output: Text list

Examples

Parser expression	Description
Syntax last(usersWhoTransitioned("Open", "In Progress"))	This example returns the name of the user who was the last to execute the transition "Start Progress", e.g.: admin.istrator To achieve this the following functions are used: last()

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
fromStatus	TEXT	Text containing a valid status name.
toStatus	TEXT	Text containing a valid status name.

Output

This function returns a

TEXT LIST

Variant where you additionally define a specific **issue key**.

Syntax

usersWhoTransitioned(fromStatus, toStatus, issueKey) #Output: Text list

Examples

Parser expression	Description
Syntax <pre>count(usersWhoTransitioned("Open", "In Progress", %{parent.key}))</pre>	This example returns the number of times the transition "Start Progress" has been executed in the parent issue, e.g. 4 To achieve this the following functions are used: count()

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
fromStatus	TEXT	Text containing a valid status name.
toStatus	TEXT	Text containing a valid status name.
issueKey	TEXT	Text containing a valid issue key. Usually field codes are used.

Output

This function returns a



Use cases and examples

Use case

No content found.