

issuesUnderEpic()

This function returns an **issue list** containing issues which are **linked to same epic as the current issue**.

The current issue will be included in the output, **except** if it is an epic itself.

Only standard issues (no sub-tasks) will be returned and duplicates are being removed.

Syntax

```
issuesUnderEpic() #Output: Issue list
```

Examples

Parser expression	Description
issuesUnderEpic()	This example returns an issue list with all issues linked to the same epic as the current issue, e.g. JWT-2, JWT-3, JWT-4

Output

This function returns an

ISSUE LIST

Variant where you additionally define **issues**.

Duplicated issues are filtered from the output.

Syntax

```
issuesUnderEpic(issueList) #Output: Issue list
```

Examples

Parser expression	Description
issuesUnderEpic(linkedIssues("is blocked by"))	This example returns an issue list of all issues linked to the same Epics as the issues blocking the current issue, e.g. JWT-2, JWT-3, JWT-4 To achieve this the following functions are used: <ul style="list-style-type: none">• linkedIssues()

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
issueList	ISSUE LIST	Any given issue list. Usually this value is retrieved from a function (e.g. linkedIssues() or issuesUnderEpic()).

Output

This function returns an

ISSUE LIST

Variant where you define **issue keys** instead.

Syntax

```
issuesUnderEpic(issueKeys) #Output: Issue list
```

Examples

Parser expression	Description
issuesUnderEpic("CRM-15, HD-21")	This example returns an issue list of issues linked to the same epics as CRM-15 and HD-21 .

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
issueKeys	TEXT	A comma separated list of issue keys.

Output

This function returns an

ISSUE LIST

If you want to **remove the given issues** from the output have a look at [siblingIssuesUnderEpic\(\)](#) instead.



Use cases and examples

Use case	JWT feature	Workflow function	Field type	Automated action	Parser functions
Close epic when stories are done				Transition issue action	count() filterByStatus() issuesUnderEpic()
Clone epic, tasks and sub-tasks		Create issue			toString() toStringList() issueKeysToIssueList() replaceFirst() first() fieldValue() textOnStringList() findModify() subtasks() issuesUnderEpic()
Total time logged on an epic			Number		sum() fieldValue() issuesUnderEpic()
Total remaining estimate in an epic (no sub-tasks)			Number		sum() fieldValue() issuesUnderEpic()
Total remaining estimate in an epic (all linked issues)			Number		sum() fieldValue() issuesUnderEpic() subtasks()
Total of all story points in an epic			Number		sum() fieldValue() issuesUnderEpic()
Block an Epic's transition until all the issues under that Epic are resolved		Logical validator Logical condition			count() issuesUnderEpic() filterByResolution()