

last()

Supported list types

[Number list](#) | [Text list](#) | [Issue list](#) | [Use cases and examples](#)

Number list

This function returns the **last** element of a **number list**.

Syntax

```
last(numberList) #Output: Number
```

Examples

Parser expression	Description
<code>%{last([3, 2, 1, 0])}</code>	This example returns: 0

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
numberList	NUMBER LIST	Any given number list.

Output

This function returns a **NUMBER**

If the number list is empty, the function returns **NULL**

Text list

This function returns the last element of a **text list**.

Syntax

```
last(textList) #Output: Text
```

Examples

Parser expression	Description
<pre>%{last(["blue", "red", "green"])} green</pre>	This example returns: green

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
textList	TEXT LIST	Any given text list.

Output

This function returns a **TEXT**

If the text list is empty, the function returns **NULL**

Issue list

This function returns an **issue list** with the last element of the given **issue list**.

Syntax

```
last(issueList) #Output: Issue list
```

Examples

Parser expression	Description
<pre>%{last(subtasks())} IT-9289</pre>	This example returns the last sub-task of the current issue, e.g.: IT-9289 To achieve this, the following functions are used: <ul style="list-style-type: none">• subtasks()

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
issueList	ISSUE LIST	Any given issue list. Usually this value is retrieved from a function (e.g. linkedIssues() or subtasks()).

Output

This function returns an

[ISSUE LIST](#)

If the issue list is empty, the function returns an empty

[ISSUE LIST](#)



Use cases and examples

Use case

No content found.
