

issuesFromJQL()

This function returns an **issue list** of issues returned by the specified **JQL query**. Visibility restrictions (permissions and issue security) might apply. This query will be run as the configured **run as user**.

Syntax

issuesFromJQL(jqlQuery) #Output: Issue list

Examples

Parser expression	Description
<code>%{issuesFromJQL("status in (Open, Done)")}</code>	This example returns an issue list with all issues that are in status " Open " or " Done ", e.g: IT-2232, IT-21233
<code>%{issuesFromJQL("'Story point estimate' is not empty")}</code>	This example returns an issue list with all issues that do have a story point estimation , e.g: IT-2321, IT-2124, IT-342

Additional information

Parameters used in this function

Parameter	Input (data type)	Description				
jqlQuery	TEXT	Any valid JQL query. ⚠ Double quotation marks in JQL have to be replaced with single quotation marks, e.g.: <table><tr><td>Usually JQL would look like</td><td>"Epic Link" is not empty</td></tr><tr><td>Using it within issuesFromJQL()</td><td>'Epic Link' is not empty</td></tr></table>	Usually JQL would look like	"Epic Link" is not empty	Using it within issuesFromJQL()	'Epic Link' is not empty
Usually JQL would look like	"Epic Link" is not empty					
Using it within issuesFromJQL()	'Epic Link' is not empty					

Output

This function returns an

ISSUE LIST

If the **JQL query** does not return a result, the function returns an empty

ISSUE LIST

 Use cases and examples

Use case

No content found.

