

Temporary text

| Field code |
|--|
| <code>%{issue.temporaryText1} ... %{issue.temporaryText5}</code> |

Read

| | |
|------------------|--|
| Returned value | Text previously stored in the temporary field |
| Output data type | <div>TEXT</div> |
| Example output | This is a text stored temporarily |

Write

| | |
|-----------------------|-----------------------------------|
| Valid text input | Unlimited text |
| Valid numerical input | Numbers are <u>cast</u> to text |
| Example input | This is a text stored temporarily |

There are **5 temporary text fields**.

- `%{issue.temporaryText1}`
- `%{issue.temporaryText2}`
- `%{issue.temporaryText3}`
- `%{issue.temporaryText4}`
- `%{issue.temporaryText5}`

These fields are used to **hold temporary text values** returned by a **post function**, which can be used in a **subsequent post function** within the same workflow transition.

Post functions using temporary text fields via additional options:

- [Create issue](#) - store issue keys from the issue(s) to be created in the field temporary text 3.
- [Send email](#) - store email information, e.g. recipients, subject or body, in the fields temporary text 1 to 5.

Please note that:

- once a **transition** execution has **ended**, all temporary fields are **cleared**.
- you **cannot** use temporary fields to pass values from **one transition to another**.