

# Only user specified in project property is allowed to execute transition

On this page

[Prerequisites](#) | [Configuration](#) | [Screenshots](#) | [Related use cases](#)

## Use case

Within JWT, **project properties** can be used to add **additional meta data** to your project, that than be later referenced throughout JWT's features.

In the following use case we use a project property to define a **user that is the only one who is allowed to execute specific transitions**.

Why should I use a project property for this?

**Why use a project property instead of defining the user to be checked against right in the condition/ validator itself?**

By using a project property for defining the user to be checked against, the **configuration can be reused in several transitions**. If then the user changes, the username must only be adapted in **one central spot** instead of going through every transition and check the configuration.



## Prerequisites

### Set up the project property

In order to get the value of the project property later on in the condition or validator, the property has first to be created.

1

Head over to the project you want to create the project property in.

2

Head over to **Project settings Details**

3

Add the following text to the **project description**:

```
{approver=<username>}
```

Replace **<username>** with the actual username you want to set as approver.



## Configuration

1

Add the [Validation of JWT project property](#) or [Condition on JWT project property](#) to the desired transition or create a new transition.

2

### Property key

Enter the name of the project property:

approver

In this case we named the project property **approver**. If you use a different name, make sure to update the above expression accordingly.

3

### Property value

Enter the following expression:

`%{system.currentUser}`

4

### Operator

Choose **is equal**

This way the transition can only be executed by the approver. Any other user won't be able to do so.

The following parameters are **only available**, if you are configuring this use case as a **validator**.

## Validator only

1

### Error message

Enter the following expression in the **Advanced text** mode:

"Only the approver (" + projectProperty("approver") + ") is allowed to execute this transition."

The function used is [projectProperty\(\)](#).



## Screenshots

[Update parameters of the Condition on JWT project property](#) Condition for this transition.

Update parameters of the Condition on JWT project property Condition for this transition.

### Basic configuration\*

Define the required parameters for this condition.

Property key\*

1 approver

Enter plain text and optionally use field codes, e.g. `%{issue.summary}`, to insert field values. The expression must return a **project property key**.

Property value\*

1 `%{system.currentUser}`

Enter plain text and optionally use **field codes**, e.g. `%{issue.summary}`, to insert field values.

Operator

is equal

Select how to compare the value against the given property key.

### Condition on JWT project property




[Documentation](#)

Evaluate the value of a JWT project property.

### Workflow

JWT 3.0.0 Use cases



## Related use cases

Use case	JWT feature	Workflow function	Parser functions	Label
Only user specified in project property is allowed to execute transition		Condition on JWT project property Validation of JWT project property	<code>projectProperty()</code>	

If you still have questions, feel free to refer to our [support](#) team.