

Field codes (automation-only)

This page lists all field codes, which are **only** available in [JWT automation rules](#).

These fields can be used to retrieve values from the event or action which is **triggering** the execution of the rule.

Example of an automation-only field code

Field code	Context	Description
<code>%{trigger.project.description}</code>	<code>trigger</code>	The description of the project triggering the automation rule.

The `trigger` prefix (or context) can be used in various places in automation rules. Other simple field codes, such as `%{issue.assignee}` can also be changed to `%{trigger.issue.assignee}` to retrieve the **assignee** from the **issue triggering** the automation rule.

The field codes listed on this page, however, are **only valid** in the context of automation rules and depend on the type of [Automation triggers](#).

Field name	Field code	Example output	Output data type	Label
Component default assignee	<code>%{trigger.component.defaultAssignee}</code>	admin.istrator	TEXT	
Component description	<code>%{trigger.component.description}</code>	This is a component	TEXT	
Component ID	<code>%{trigger.component.id}</code>	10000	TEXT	
Component lead	<code>%{trigger.component.lead}</code>	admin.istrator	TEXT	
Component name	<code>%{trigger.component.name}</code>	Customer Relationship Management Component	TEXT	
Project category (trigger)	<code>%{trigger.project.category}</code>	Archive	TEXT	
Project description (trigger)	<code>%{trigger.project.description}</code>	This is the CRM project	TEXT	
Project key (trigger)	<code>%{trigger.project.key}</code>	CRM, HR, SDESK	TEXT	
Project lead's email (trigger)	<code>%{trigger.project.leadEmail}</code>	user@example.com	TEXT	
Project lead's full name (trigger)	<code>%{trigger.project.leadDisplayName}</code>	Bob Smith	TEXT	
Project lead (trigger)	<code>%{trigger.project.lead}</code>	admin.istrator	TEXT	
Project name (trigger)	<code>%{trigger.project.name}</code>	Customer Relationship Management	TEXT	
Project URL (trigger)	<code>%{trigger.project.url}</code>	https://www.decadis.de/x	TEXT	
User directory ID	<code>%{trigger.user.directoryId}</code>	10001	TEXT	

User directory user	%{trigger.user.directoryUser}	admin.istrator	TEXT
User email	%{trigger.user.email}	user@example.com	TEXT
User full name	%{trigger.user.fullName}	Bob Smith	TEXT
User ID	%{trigger.user.id}	10000	TEXT
User is active	%{trigger.user.isActive}	true, false	TEXT
User key	%{trigger.user.key}	admin.istrator	TEXT
User name	%{trigger.user.name}	admin.istrator	TEXT
Version archived	%{trigger.version.archived}	true, false	TEXT
Version description	%{trigger.version.description}	This is version 1.0	TEXT
Version ID	%{trigger.version.id}	10000	TEXT
Version name	%{trigger.version.name}	Version 1.0	TEXT
Version project	%{trigger.version.project}	CRM	TEXT
Version project ID	%{trigger.version.projectId}	10000	TEXT
Version released	%{trigger.version.released}	true, false	TEXT
Version release date	%{trigger.version.releaseDate}	2020-02-17 07:46	TEXT
Version sequence	%{trigger.version.sequence}	1	TEXT
Version start date	%{trigger.version.startDate}	2020-02-17 07:46	TEXT

If you still have questions, feel free to refer to our [support](#) team.