

projectIDFromKey()

This function returns the **internal ID** of a given **project key**, or a comma-separated list of project keys.

Syntax

```
projectIDFromKey(projectKeys) #Output: Text
```

Examples

Parser expression	Description
<p>Syntax</p> <pre>projectIDFromKey("DEMO")</pre>	<p>This example returns a text representing the internal ID of the project with the key "DEMO", e.g.:</p> <p>10001</p>
<p>Syntax</p> <pre>projectIDFromKey(%{issue.project.key})</pre>	<p>This example returns the internal ID of the current issue's project, e.g.:</p> <p>10005</p>
<p>Syntax</p> <pre>projectIDFromKey(toString(distinct(fieldValue(%{issue.project.key}, linkedIssues()))))</pre>	<p>This example returns a all internal IDs of projects from linked issues, e.g.:</p> <p>10000, 10003</p> <hr/> <h3>More info...</h3> <p>Steps in this example:</p> <ol style="list-style-type: none">1. Use linkedIssues() to get all issues linked to the current issue2. Use fieldValue() to get the project key from the linked issues3. Use distinct() to remove duplicate keys4. Use toString() to convert the returned text list to a text with comma separated keys

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
projectKeys	<input type="text" value="TEXT"/>	Text containing project keys in a comma-separated list.

Output

This function returns a



Use cases and examples

Use case

No content found.
