

userFullName()

This function returns the **display name** for a given user name.

Syntax

userFullName(userName) #Output: Text

Examples

Parser expression	Description
<code>userFullName(%{system.currentUser})</code>	This example returns the display name the current user, e.g.: Bob Smith

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
userName	TEXT	Text containing a valid user name.

Output

This function returns a

Variant for **multiple** users.

Syntax

userFullName(userList) #Output: Text list

Examples

Parser expression	Description
<code>toString(userFullName(toStringList(%{issue.watcher})))</code>	This example returns the display names of all watchers. To achieve this, the following functions are used: • toStringList() • toString()

```
toString(userFullName(["b.smith", "d.jones"]))
```

This example returns the display names of all **two users**, e.g.:

Bob Smith, Dave Jones

To achieve this, the following functions are used:

- [toString\(\)](#)

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
userList	TEXT LIST	Any valid text list.

Output

This function returns a

If you want to return the **user name** instead of a display name, check out: [fullNameToUser\(\)](#)



Use cases and examples

Use case	JWT feature	Workflow function	Field type	Automated action	Parser functions
Last commenter's full name			Text		userFullName()
Last comment, its author, and timestamp			Text		userFullName() dateToString() last() allCommentDates()