componentLeads()

This function returns the **user name** of a **component lead** of a specified component.

You can also provide a comma-separated list of components and the function returns a comma-separated list of **user names**.

The output will contain duplicate user names if the same user is a lead of more than one component.

Syntax
`componentLeads(components) #Output: Text`

Examples

Parser expression	Description
`componentLeads("UI")`	This example returns the name of the component lead of the **UI component** associated with the current issue, e.g. **admin.istrator**
`componentLeads(%{issue.components})`	This example returns a comma-separated text with the **user names** of the all component leads for components associated with the current issue, e.g.: **admin.istrator, bob.smith**

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
`components`	TEXT	Text including a component name or a comma-separated list of component names.

Output

This function returns a TEXT

Variant where you can additionally define a **project key**

Syntax
`componentLeads(components, projectKey) #Output: Text`

Examples

Parser expression	Description
`componentLeads("Web Portal", "CRM")`	The function returns the **user name** of the **Web Portal** component lead for the **CRM project**, e. g.: **admin.sitrator**

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
`components`	TEXT	Text including a component name or a comma-separated list of component names.
`projectKey`	TEXT	Text including a project key.

Output

This function returns a TEXT

Use cases and examples

Use case
No content found.