
allIssuesUnder()

This function returns an **issue list** containing all descendant issues, i.e., all related issues located in any level below **current issue** according to **Advanced Roadmaps hierarchy**.

Advanced Roadmaps hierarchy includes:

- Issues linked by **Parent Link** custom field.
- Issues linked by **Epic-Story** link.
- **Sub-tasks** in the **lowest level** of the hierarchy. Sub-tasks under issues in intermediate levels of the hierarchy are not considered to belong to **Advanced Roadmaps hierarchy.**

Example:



Syntax
`allIssuesUnder() #Output: Issue list`

Examples

Parser expression	Description
`allIssuesUnder()`	Considering that current issue is *JWT-3*, this expression returns all issues in any level below it: **JWT-2, JWT-11, JWT-7, JWT-4, JWT-12, JWT-6, JWT-10, JWT-13**

Output

This function returns an ISSUE LIST

Variant where you additionally define **issues**.

Duplicated issues are filtered from the output.

Syntax
`allIssuesUnder(issueList) #Output: Issue list`

Examples

Parser expression	Description
`allIssuesUnder (linkedIssues("is blocked by"))`	Assuming that expression `linkedIssues("is blocked by")` returns `[JWT-4, JWT-8]`, this example returns all the children issues in any level below issues *JWT-3* and *JWT-4*: **JWT-6, JWT-10, JWT-9, JWT-16** To achieve this the following functions are used: • linkedIssues()

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
`issueList`	ISSUE LIST	Any given issue list. Usually this value is retrieved from a function (e.g. linkedIssues() or issuesUnderEpic()).

Output

This function returns an ISSUE LIST

Variant where you define **issue keys** instead.

Duplicated issues are filtered from the output.

Syntax
`allIssuesUnder(issueKeys) #Output: Issue list`

Examples

Parser expression	Description
`allIssuesUnder("JWT-3, JWT-8")`	This example returns all issues in any level below issues *JWT-3* and *JWT-8*: **JWT-2, JWT-11, JWT-7, JWT-4, JWT-12, JWT-6, JWT-10, JWT-13,JWT-9, JWT-16**

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
`issueKeys`	TEXT	A comma separated list of issue keys.

Output

This function returns an ISSUE LIST

To return **the issues just under an issue** within the Advanced Roadmaps hierarchy, you might want to have a look into the issuesUnder() function.

To return **all issues having the same parent** within the Advanced Roadmaps hierarchy, you might want to have a look into the siblingIssues() function.

To return **the parent of an issue** within the Advanced Roadmaps hierarchy, you might want to have a look into the parent() function.

To return **all issues above an issue** within the Advanced Roadmaps hierarchy, you might want to have a look into the issuesAbove() function.

Use cases and examples

Use case
No content found.