

issueKeysToIssueList()

This function converts a **text** with comma-separated **issue keys** into an **issue list**.

Learn more about [lists](#).

Syntax

```
issueKeysToIssueList(issueKeys) #Output: Issue list
```

Examples

Parser expression	Description
issueKeysToIssueList("CRM-12, HT-254")	This example returns an issue list of issues with keys CRM-12 and HT-254 : ["CRM-12", "HT-254"]

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
issueKeys	TEXT	A text with a comma-separated list of issue keys .

Output

This function returns an ISSUE LIST

Use cases and examples

Use case	JWT feature	Workflow function	Field type	Automated action	Parser functions
Add links to the issues in a ScriptRunner Issue Picker field				Create issue link action Delete issue link action	issueKeysToIssueList() toString() toStringList() replaceAll() previousValue()
Link to the linked epic from the current issue			Text		toString() fieldValue() issueKeysToIssueList()
Clone epic, tasks and sub-tasks			Create issue		toString() toStringList() issueKeysToIssueList() replaceFirst() first() fieldValue() textOnStringList() findModify() subtasks() issuesUnderEpic()

Track issues mentioned
in comments



Create issue
link action

`findPattern()`
`issueKeysToIssueList()`
`toString()`