

usersWhoTransitioned()

This function returns the names of the users who transitioned the current issue from a **given status** to another **given status**, ordered by ascending transition time.

An empty text as an argument is interpreted as **any status**.

Syntax

```
usersWhoTransitioned(fromStatus, toStatus) #Output: Text list
```

Examples

Parser expression	Description
<div>Syntax <pre>last(usersWhoTransitioned("Open", "In Progress"))</pre></div>	<p>This example returns the name of the user who was the last to execute the transition "Start Progress", e.g.:</p> <p>admin.istrator</p> <p>To achieve this the following functions are used:</p> <ul style="list-style-type: none">• last()

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
fromStatus	<input type="text" value="TEXT"/>	Text containing a valid status name.
toStatus	<input type="text" value="TEXT"/>	Text containing a valid status name.

Output

This function returns a

Variant where you additionally define a specific **issue key**.

Syntax

```
usersWhoTransitioned(fromStatus, toStatus, issueKey) #Output: Text list
```

Examples

Parser expression	Description
<div>Syntax</div> <pre>count(usersWhoTransitioned("Open", "In Progress", %{parent.key}))</pre>	<p>This example returns the number of times the transition "Start Progress" has been executed in the parent issue, e.g.</p> <p>4</p> <p>To achieve this the following functions are used:</p> <ul style="list-style-type: none"> <code>count()</code>

Additional information

Parameters used in this function

Parameter	Input (data type)	Description
fromStatus	TEXT	Text containing a valid status name.
toStatus	TEXT	Text containing a valid status name.
issueKey	TEXT	Text containing a valid issue key. Usually field codes are used.

Output

This function returns a TEXT LIST

Use cases and examples

Use case

No content found.