# Migrate 'Compare two values condition'

The Compare two values condition of JWT DC is also available for JWT Cloud.

Since JWT DC field codes are not available in conditions or validators in JWT Cloud, they have to be replaced by their Jira expression equivalent.

### Migration steps



Add the Compare two values condition.



Reconfigure the condition with the help of the following list, providing the necessary basics.

## Migration details

<b>≌</b> JWT	JWT Cloud parameter DC parameter		Notes
Left-hand side value	Field		
	Fields		While this value is set by a parser expression in JWT DC, it is selected from a drop-down list in JWT Cloud.
	The following list presents the fields supported by the Compare two values condition in JWT Cloud. Fields not appearing in this list, cannot be mapped to JWT Cloud. All fields are available for the contexts "issue" and "parent".		
	JWT DC field	JWT Cloud field	
	Affects version/s	Affects version/s	
	Assignee	Assignee	
	Assignee's full name	Assignee's full name	
	Attachments	Attachments	
	Component/s	Component/s	
	Creator	Creator	
	Creator's full name	Creator's full name	
	Current date and time	Current date and time	
	Current user	Current user	
	Current user's full name	Current user's full name	
	Date and time of creation	Date and time of creation	
	Date and time of last update	Date and time of last update	
	Date and time of resolution	Date and time of resolution	
	Description	Description	

Due date	Due date
Environment	Environment
Fix version/s	Fix version/s
Issue key	Issue key
Keys of linked issues	Issue links
Issue status	Issue status
Issue status category	Issue status category
Issue type	Issue type
Labels	Labels
Last comment	Last comment
Last commenter	Last commenter
Number of affects version/s	Number of affects version/s
Number of attachments	Number of attachments
Number of fix version/s	Number of fix version/s
Number of labels	Number of labels
Number of linked issues	Number of linked issues
Number of sub-tasks	Number of sub-tasks
Number of votes received	Number of votes received
Original estimate (minutes)	Original estimate (minutes)
Priority	Priority
Project key	Project key
Project name	Project name
Remaining estimate (minutes)	Remaining estimate (minutes)
Reporter	Reporter
Reporter's full name	Reporter's full name
Resolution	Resolution
Date and time of resolution	Resolution date
Security level	Security level
Keys of sub-tasks	Subtasks
Summary	Summary
Total time spent (minutes)	Total time spent (minutes)
Watchers	Watchers
All custom field types	All custom field types provided by JWT DC except <b>Text Field (read-only)</b>

Right-hand side value

Comparison value

## Fields

Either a field can be selected or a value can be set manually. In JWT Cloud one of these options has to be selected first and then a field or a value by using the parser expression editor has to be provided.

The following list presents the fields supported by the Compare two values condition in JWT Cloud. Fields not appearing in this list, cannot be mapped to JWT Cloud. All fields are available for the contexts "issue" and "parent".

JWT DC field	JWT Cloud field
Affects version/s	Affects version/s
Assignee	Assignee
Assignee's full name	Assignee's full name
Attachments	Attachments
Component/s	Component/s
Creator	Creator
Creator's full name	Creator's full name
Current date and time	Current date and time
Current user	Current user
Current user's full name	Current user's full name
Date and time of creation	Date and time of creation
Date and time of last update	Date and time of last update
Date and time of resolution	Date and time of resolution
Description	Description
Due date	Due date
Environment	Environment
Fix version/s	Fix version/s
Issue key	Issue key
Keys of linked issues	Issue links
Issue status	Issue status
Issue status category	Issue status category
Issue type	Issue type
Labels	Labels
Last comment	Last comment
Last commenter	Last commenter
Number of affects version/s	Number of affects version/s
Number of attachments	Number of attachments
Number of fix version/s	Number of fix version/s
Number of labels	Number of labels
Number of linked issues	Number of linked issues
Number of sub-tasks	Number of sub-tasks
Number of votes received	Number of votes received
Original estimate (minutes)	Original estimate (minutes)
Priority	Priority
Project key	Project key
Project name	Project name

Resolution  Date and time of resolution	Resolution Resolution date
Security level	Security level
Keys of sub-tasks	Subtasks
Summary	Summary
Total time spent (minutes)	Total time spent (minutes)
Watchers	Watchers
All custom field types	All custom field types provided by JWT DC except Text Field (read-only)

#### Operator

#### Operator

JWT DC operator	JWT Cloud operator
=	=
!=	!=
<	<
>	>
<=	<=
>=	>=

Depending on the field which is selected as left-hand value, not all operators are valid for this field. Only the valid ones are offered.

JWT Cloud offers the two additional operators  $\sim$  (contains) and ! $\sim$  (does not contain) which may be used instead of the ones selected in the JWT DC configuration.

Due to the different architecture, it may happen that the condition gets too complex. This is the case when many fields are checked. The condition cannot be saved, and a corresponding error message will be displayed. If that's the case, the condition has to be split up into two or more

If you still have questions, feel free to refer to our support team.